

DOOSAN HEAVY EXCAVATOR ATTACHMENTS

Doosan's portfolio of Attachments are designed to work in all types of working applications. The new range of DOOSAN attachments which are offered, are developed based on customer's requirements and satisfaction criteria through worldwide market feedback. The attachments series consists of demolition, material handling, earth moving and connecting attachments.



HYDRAULIC BREAKER



ROTATING CRUSHER



FIXED PULVERIZER



VIBRATING RIPPER



PILE DRIVER



MULTI-PROCESSOR



STEEL SHEAR



MULTI-GRAPPLE



STONE GRAPPLE

DOOSAN HEAVY EXCAVATOR ATTACHMENTS USING THE 6 KINDS OF GOOD REASONS



ONE-STOP SHOP

One place for complete solutions :
(carrier + attachments + parts + service)



ENGINEERING APPROVED

Optimized for DOOSAN equipment high efficiency and performance, resulting in lower running and maintenance cost.



SERVICE

Broad coverage via the DOOSAN service network, fully supported by DOOSAN product specialists.



QUALITY

Products manufactured to highest standards.



WARRANTY

Avoid compatibility issues and operating differences from using Non-approved attachments.



PLUG & PLAY READINESS

Easy to install and operate.



RIPPER



PLATE COMPACTOR



CLAMSHELL BUCKET



HYDRAULIC QUICK COUPLER



ORANGE GRAPPLE



LOG GRAPPLE



WOOD GRAPPLE

Demolition Attachments

ROTATING CRUSHER

Product



Reversible rectangular blades



Hardened teeth
High spec. materials for enhanced durability.



Increased jaw opening
To crush large sections.



Hydraulic 360° rotation unit
Allowing fast and targeted positioning to materials.



Adjustable Speed control valve
Delivering maintenance efficiency.



Trunnion type cylinder
The entire operation from RC25 and bigger.

Doosan Rotating Crushers are designed for both primary demolition work and secondary concrete reduction. Especially for secondary demolition, it is ideal for breaking out concrete from fixed structure, pulverizing concrete, separating different materials for recycling, cutting reinforced rods and small steel profile, and working with high reach boom.



Feature & Benefits

4 different models

- 13-36 tons Models are available.

Trunnion-supported type cylinder

- Offers high breaking forces throughout the entire working cycle as well as stable movement.

Hydraulic 360° rotation unit

- Limitless rotation for fast and targeted positioning in all conditions.

Adjustable Speed control valve with cylinder

- Maximum maintenance efficiency and working speed.

Customized Blades and Tooth System

- Optimized tooth arrangement.
- Fully replaceable rectangular blades and bolting tooth.

Wider opening jaw

- Easily operates for a large demolition job.

High grade material composition for better durability

- Used HB360-600 grade material on replaceable parts.

Model		RC14	RC22	RC25	RC34
Carrier weight	t	13~16	17~25	20~27	28~36
Operating weight	kg	1,250	1,780	2,300	2,950
Overall Length	mm	1,840	2,078	2,474	2,686
Jaw width (Fixed/Moving jaw)	mm	384/330	438/350	470/346	532/370
Max jaw opening	mm	720	732	925	1,056
Max. operating pressure	bar	350	350	350	350
Crushing force (Tip)	t	51	56	67	78
Cutter blade Length	mm	240	240	360	360
Required oil flow	lpm	100~180	150~250	150~250	200~300
Speed control value		-	●	●	●
Bolting tooth		-	-	●	●